



extend your
outdoor lifestyle



New Zealand's
highest performing
polycarbonate roofing



New Zealand's first choice in outdoor living area enhancement and protection.

Available in three proven options to suit your lifestyle.



Cost-effective Roofing Solution

Profiled translucent roofing product designed for weather protection and enhancement of your outdoor living area.

- Provides protection from sun, rain and wind
- Applications: use in a variety of roofing, cladding and fencing situations.
- Provides 99.9% protection from UV rays



	clear	opal	bronze tint	grey tint	diffused opal**
Light Transmission %	93%	49%	38%	19%	16.2%
Heat Reduction % ‡	0%	52%	25%	40%	18%



Sheet lengths available: 1.8m, 2.1m, 2.4m, 2.7m, 3.0m, 3.6m, 4.2m, 4.8m, 5.4m, 6.0m, 7.2m

Sheet Width: Corrugated 840mm, Greca 810mm, 5-rib 830mm

Cover Width: Corrugated 755mm, Greca 760mm, 5-rib 762mm

**NB: Opal and Diffused Opal not available in 5 Rib profile.

Classic – Performance & Reliability

The classic, high-performance Laserlite® range

- Certified to NZ and Australian standards.
- Extend the life of the sheet by up to 50%#
- Maintain sheet colour and clarity up to 50% longer#
- Provide 99.9% protection from UV rays up to 50% longer#
- Resist 25% larger hailstones#

As compared to other profiled polycarbonate roofing products



	clear	bronze tint	grey tint
Light Transmission %	93%	38%	19%
Heat Reduction % ‡	0%	33%	47%



Sheet lengths available: 1.8m, 2.1m, 2.4m, 2.7m, 3.0m, 3.6m, 4.2m, 4.8m, 5.4m, 6.0m, 7.2m

Sheet Width: Corrugated 840mm, Greca 810mm, 5-rib 830mm

Cover Width: Corrugated 755mm, Greca 760mm, 5-rib 762mm




Premium – Ultimate Comfort

Technologically advanced heat reflective range for the ultimate outdoor lifestyle experience.

- Certified to NZ and Australian standards.
- Up to 50% better heat reduction than standard profiled polycarbonate sheet#
- Reduced glare for ultimate comfort

As compared to other profiled polycarbonate roofing products



	frost	platinum*
Light Transmission %	47%	18%
Heat Reduction % ‡	63%	69%



Sheet lengths available: 1.8m, 2.1m, 2.4m, 2.7m, 3.0m, 3.6m, 4.2m, 4.8m, 5.4m, 6.0m, 7.2m

Sheet Width: Corrugated 840mm, Greca 810mm

Cover Width: Corrugated 755mm, Greca 760mm

*NB: Platinum is only available in Greca profile.

‡Based on the warming effect of the sun's rays through a sheet vs 3mm float glass (300-2500nm)



- All Laserlite® products can easily be cut to measure.
- Laserlite® is engineered and built using only 100% Makrolon® Resin.
- Refer to full warranty terms & conditions at www.alsynite.co.nz or from an Alsynite One NZ office.




ADVANCED WEATHERGUARD™



UV rays, wind, hail and rain have the potential to make polycarbonate resins brittle and lose colour over time. **Advanced Weatherguard™** protects the sheet and protects from harmful UV radiation

COMFORT COOL™



Infra red light emitted by the sun passes through polycarbonate sheet making it warm underneath. **Comfort Cool™** Technology reflects the heat away whilst letting visible light through with less glare.

Comfort level under Laserlite®



Light level under Laserlite®



Accessories



FASTENERS: We recommend using Laserlite® One Shot® Fasteners to fix your Laserlite® polycarbonate roofing.


OneShot® Fasteners have a built-in cutting device that will pre-drill an expansion hole while you drill in the fastener. The expansion hole is very important because it allows the sheet to expand and contract when the temperature changes.

Can be used up to and including high wind zones (please see www.alsynite.co.nz for installation instructions).

FOAMS AND TAPES:



Back Channel Infill Strip



Noise Stop Tape

FLASHINGS:

- Range of Polycarbonate Flashings
- Laserlite Lap Connectors



For full range of available accessories, please visit our website www.alsynite.co.nz

NZBC Fire Group 1-S Rating




Laserlite® has been extensively tested using the full scale ISO 9705 room test. This extensive testing utilises a gas burner exposing the sheeting to 100kw for 10 minutes, and then 300kw for a further 10 minutes. Laserlite® achieves a NZBC 1-S Rating as flashover is not reached.



Protecting the environment, Laserlite® is fully recyclable and no waste is created in the production process. Laserlite® is also heavy metal free. See website for further details.




ISO 9001



WWW.JAS-ANZ.ORG/REGISTER



SCAN. EXPLORE.



0800 257 964

www.alsynite.co.nz

FIND YOUR PRODUCT.

or go to:
www.laserlite.alsynite.co.nz